



| 1" 1.4/16mm C | | 1" | 2/3" | 1/1.8" |
|------------------------------------------|------------|------------------------------|-----------|--------------------|
| FOCAL LENGTH | | f=16mm | | |
| MAX. DIAMETER (RATIO) | | F=1 : 1.4~16 | | |
| PICTURE SIZE | | 9.6x12.8mm | 6.6x8.8mm | 5.4x7.2mm |
| ANGLE | VER. ANGLE | 33.6° | 23.2° | 19.0° |
| | HOR. ANGLE | 44.3° | 30.8° | 25.3° |
| | DIA. ANGLE | 54.3° | 38.3° | 31.5° |
| DISTORTION (TV) | | -1.0% | | |
| SHOOTING RANGE AT MINIMUM FOCUS DISTANCE | VER. | 186.2mm | 126.8mm | 103.4mm |
| | HOR. | 251.5mm | 170.3mm | 138.6mm |
| | DIA. | 318.3mm | 214.6mm | 174.3mm |
| MINIMUM FOCUS DISTANCE | | 0.3m | | |
| FLANGE BACK | | 17.526mm in air | | |
| BACK FOCUS | | 12.6mm in air | | |
| FILTER SCREW SIZE | | M35.5x0.5 | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT ϕ 21.5mm | | REAR ϕ 18.8mm |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | -128.5mm | | |
| TEMPERATURE RANGE | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | CENTER \varnothing 20lp/mm | | CORNER 80lp/mm |
| WEIGHT | | 150 g | | |

NOTE: Specifications and availability are subject to change without notice



| | | | |
|------------|--|----------------|---------|
| | | 1/1 | HR977SW |
| | | 1" F1.4 f=16mm | |
| 2015.7.30 | | LM16HC-SW | |
| 2014.12.25 | | | |
| 2013.4.15 | | | |