



|                           |            |                         |        |                    |
|---------------------------|------------|-------------------------|--------|--------------------|
| 2/3" 2/35mm C             |            | 2/3"                    | 1/1.8" | 1/2"               |
| FOCAL LENGTH              |            | f=35mm                  |        |                    |
| MAX. DIAMETER (RATIO)     |            | F=1:2.0~16              |        |                    |
| PICTURE SIZE              |            | 6.6x8.8mm               |        |                    |
| ANGLE                     | VER. ANGLE | 10.8°                   | 8.8°   | 7.9°               |
|                           | HOR. ANGLE | 14.4°                   | 11.8°  | 10.5°              |
|                           | DIA. ANGLE | 17.9°                   | 14.7°  | 13.1°              |
| DISTORTION (TV)           |            | -0.2%                   |        |                    |
| SHOOTING RANGE AT         | VER.       | 35.8mm                  | 29.3mm | 26.0mm             |
|                           | HOR.       | 47.9mm                  | 39.1mm | 34.7mm             |
|                           | DIA.       | 60.0mm                  | 49.0mm | 43.5mm             |
| MINIMUM FOCUS DISTANCE    |            | 0.2m                    |        |                    |
| FLANGE BACK               |            | 17.526mm in air         |        |                    |
| BACK FOCUS                |            | 20.1mm in air           |        |                    |
| FILTER SCREW SIZE         |            | M27x0.5                 |        |                    |
| FRONT/REAR EFFECTIVE DIA. |            | FRONT $\phi$ 21.5mm     |        | REAR $\phi$ 11.7mm |
| MOUNT                     |            | C-MOUNT                 |        |                    |
| EXIT PUPIL                |            | -38.8mm                 |        |                    |
| TEMPERATURE RANGE         |            | -10~+50°C               |        |                    |
| STORAGE TEMPERATURE RANGE |            | -40~+60°C               |        |                    |
| RESOLUTION CENTER/CORNER  |            | CENTER 120lp/mm         |        | CORNER 100lp/mm    |
| LENS COATING              |            | WIDE BAND MULTI COATING |        |                    |
| WEIGHT                    |            | 70 g                    |        |                    |

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。



|            |       |     |                  |      |                     |
|------------|-------|-----|------------------|------|---------------------|
|            |       | 尺度  | 1/1              | 工場番号 | HR1152<br>(S10-498) |
|            |       | 機種名 | 2/3" F2.0 f=35mm |      |                     |
|            |       | 機種番 | LM35JC3M2 外觀図    |      |                     |
| 2016.09.29 | 作成年月日 |     |                  |      |                     |